

Atrust

Atrust 14" Mobile Thin Client mt182W



- | | | |
|---|--|---|
| 1 Web Camera
Built-in web camera. | 6 Touchpad
Built-in pointing device for control and input. | 11 Kensington Lock Slot
Connects a Kensington cable to secure the mobile thin client. |
| 2 Power Button
Press to turn on the client. | 7 DC IN
Connects to an AC adaptor. | 12 Nano SIM Card Slot (Option)
with 4G LTE module. |
| 3 Keyboard
Built-in keyboard for control and input. | 8 HDMI
Connects to external display. | 13 USB 3.1 Gen 1 Type-C
Connects to a USB device. |
| 4 Fingerprint Reader
Built-in fingerprint reader. | 9 USB 3.1 Gen 1 Type-C
Connects to a USB device. | 14 USB 3.1 Gen 1 Type-A
Connects to a USB device. |
| 5 Speakers
Built-in Speaker for audio output. | 10 Audio Combo
Connects to a set of headphones system. | 15 USB 3.1 Gen 1 Type-A
Connects to a USB device. |

Atrust mt182W Features



- | | |
|--|--|
| Low total cost of ownership
Additional computing access is as simple as adding more thin client devices. The total cost of ownership is then drastically reduced. | Rich remote user experience
Support Citrix® HDX/ICA™, Microsoft® RDP™ with RemoteFX™ and VMware® Horizon View™, this device can provide a rich and efficient computing experience. |
| Simple click and play
Connects this device to the host server with a Remote Session connection. Just click the shortcut for a Remote Desktop session, you can immediately start a session and enjoy the computing resources. | Easy management and maintenance
Since all computing tasks are mainly performed on a server, all hardware and software issues are significantly reduced on the client side. All user management, software installations, system management, and upgrades are done on a single server. |

Atrust mt182W Mobile Thin Client

System	
Processor	Intel® Braswell Quad Core X5-E8000 1.04G(Burst to 2.0G)
Memory	
System memory	4GB
Flash memory	32GB
Display	
LCD Type/Resolution	14" / 1920 x 1080 FHD
I/O Interfaces	
I/O ports	1 x HDMI, 2 x USB 3.1 Gen 1 Type-A, 2 x USB 3.1 Gen 1 Type-C, 1 x Audio Combo, 1 x DC IN, 1 x Fingerprint Reader, 1 x Web Camera, 2 x 2W Internal speaker, 1 x Internal microphone
Networking	
Ethernet	USB 3.1 to Gigabit Ethernet Adapter
Wireless	IEEE 802.11ac/a/b/g/n, BlueTooth v4.2 Nano SIM card slot with 4G LTE module(Optional)
Dimensions / Weight	
Dimensions	(W) 322 x (D) 222 x (H) 15.95 mm
Weight	1.2 kg (approximate)
Environment	
Operating temperature	5°C ~ 35°C
Non-operating temperature	-20°C ~ 60°C
Operating humidity (Rh)	10% ~ 90% (non-condensing)
Non-operating humidity (Rh)	5% ~ 95% (non-condensing)
AC Adaptor	
Operating voltage range	100 ~ 240 VAC
Rated line frequency	50 ~ 60 Hz
AC Adaptor	19V, 65W, 3.42A
Battery capacity	3290 mAh NOTE : The battery charges very slow under 10 degrees Celsius (50 degrees Fahrenheit) or above 35 degrees Celsius (95 degrees Fahrenheit). This is a natural limitation of battery cell technology. It is recommended to charge your battery above 10 degrees Celsius (50 degrees Fahrenheit) and under 35 degrees Celsius (95 degrees Fahrenheit). Note: Tolerance ±2°C
Software	
Operating system	Windows® 10 IoT Enterprise 2016 LTSB
Management	Atrust Device Manager (ADM) / Atrust Client Setup (ACS)
Protocols	Citrix® ICA/HDX™, Microsoft® RDP™ with RemoteFX™, VMware® Horizon View™
Manufacturing option	Nano SIM card slot with 4G LTE module

© 2018 Atrust Computer Corp. The information contained herein is subject to change without notice. Atrust shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies. Citrix and ICA/HDX are trademarks of Citrix Systems, Inc.. VMware and Horizon View are trademarks of VMware, Inc.. To learn more, visit www.atrustcorp.com.